

Applicant : Mark Molitor
Serial No. : 10/757,897
Page : 2

In the Claims

Please amend claims 1, 6-8, 11-13, 21, 24, 25, and 28, and add new claim 32 as follows.

1. (currently amended) A vehicle suspension assembly, comprising:

a first control arm having a first end and a second end, wherein the first end of the first control arm ~~is adapted to be pivotally coupled~~ includes a first bushing adapted to pivotally couple the first control arm to a first frame member of a vehicle, and wherein the second end of the first control arm is adapted to be pivotally coupled to an axle of ~~the~~ a vehicle;

a second control arm having a first end and a second end, wherein the first end of the second control arm ~~is adapted to be pivotally coupled~~ includes a second bushing adapted to pivotally couple the second control arm to a second frame member of the vehicle, and wherein the second end of the second control arm is adapted to be pivotally coupled to ~~the~~ an axle of the vehicle;

a rigid first torsional member coupled to the first control arm along a length of the first control arm rearward of the first bushing and forward of an axle, and coupled to the second control arm along a length of the second control arm rearward of the second bushing and forward of an axle; and

a third control arm having a first end and a second end, wherein the first end of the third control arm is adapted to be pivotally coupled to a third frame member of ~~the~~ a vehicle, and wherein the second end of the third control arm is adapted to be pivotally coupled to at least a select one of the second frame members and ~~the~~ an axle of ~~the~~ a vehicle.

2. (original) The vehicle suspension assembly of claim 1, wherein the first torsional member is fixedly coupled to the first control arm proximate the first end of the first control arm, and wherein the torsional member is fixedly coupled to the second control arm proximate the first end of the second control arm.

Applicant : Mark Molitor
Serial No. : 10/757,897
Page : 3

3. (original) The vehicle suspension assembly of claim 1, wherein the first torsional member is tube-shaped.

4. (original) The vehicle suspension assembly of claim 1, wherein the first end of the first control arm is adapted to be pivotally coupled with a first linkage member that is fixedly attached to and extends downwardly from the first frame member.

5. (original) The vehicle suspension assembly of claim 4, wherein the first end of the second control arm is adapted to be pivotally coupled with a second linkage member that is fixedly attached to and extends downwardly from the second frame member.

6. (currently amended) The vehicle suspension assembly of claim 5, wherein the second end of the third control arm is adapted to be pivotally coupled with a third linkage member that is fixedly attached to and extends upwardly from ~~the~~ an axle.

7. (currently amended) The vehicle suspension assembly of claim 1, wherein the first bushing of the first ~~and second~~ end of the first control arm and the second bushing of the first ~~and second~~ end of the second control arm each include an elastically deformable bushing are each elastically deformable, and wherein the second end of the first control arm and the second control arm each include an elastically deformable bushing.

8. (currently amended) The vehicle suspension assembly of claim 7, wherein the bushings of the first and second ends of the first ~~[[,]]~~ and second ~~and third~~ control arms each have an aperture extending therethrough, and wherein each aperture is elongated.

9. (original) The vehicle suspension assembly of claim 7, wherein the first and second end of the third control arm each include an elastically deformable bushing.

Applicant : Mark Molitor
Serial No. : 10/757,897
Page : 4

10. (original) The vehicle suspension assembly of claim 1, wherein the first torsional member includes a first flanged end and a second flanged end, and the first flanged end is fixedly coupled to the first control arm via at least one bolt extending through at least one aperture in the first flanged end and at least one aperture in the first control arm, and wherein the second flanged end is fixedly coupled to the second control arm via at least one bolt extending through at least one aperture in the second flanged end and at least one aperture in the second control arm.

11. (currently amended) The vehicle suspension assembly of claim 1, further including:

a first pneumatic suspension bag adapted to be positioned between the first frame member and ~~the~~ an axle; and

a second pneumatic suspension bag adapted to be positioned between the second frame member and ~~the~~ an axle.

12. (currently amended) The vehicle suspension assembly of claim 11, further including:

a third pneumatic suspension bag positioned between the first frame member and ~~the~~ an axle; and

a fourth pneumatic suspension bag positioned between the second frame member and ~~the~~ an axle.

13. (currently amended) The vehicle suspension assembly of claim 1, further including:

a fourth control arm having a first end and a second end, wherein the first end of the fourth control arm is adapted to be pivotally coupled to the third frame member of ~~the~~ a vehicle, and wherein the second end of the fourth control arm is adapted to be pivotally coupled to ~~the~~ an axle of ~~the~~ a vehicle.

Applicant : Mark Molitor
Serial No. : 10/757,897
Page : 5

14. (original) The vehicle suspension assembly of claim 13, further including:

a rigid second torsional member fixedly attached to the third control arm along a length of the third control arm, and fixedly attached to the fourth control arm along a length of the fourth control arm.

15. (original) The vehicle suspension assembly of claim 1, wherein the first and the second control arms are each substantially L-shaped defining an elbow along the length of each of the control arms.

16. (original) The vehicle suspension assembly of claim 15, wherein the first torsional member is fixedly coupled to the first and second control arms proximate the elbows thereof.

17. (original) The vehicle suspension assembly of claim 1, wherein the second end of the first control arm and the second end of the second control arm are each substantially fork-shaped.

18. (original) The vehicle suspension assembly of claim 1, wherein the torsional member is pivotably coupled to the first control arm, and wherein the first torsional member is pivotably coupled to the second control arm.

19. (original) The vehicle suspension assembly of claim 18, wherein the first torsional member is pivotable with respect to the first and second control arms in a substantially vertical direction.

20. (original) The vehicle suspension assembly of claim 18, wherein the first torsional member is pivotable with respect to the first and second control arms in a substantially horizontal direction.

Applicant : Mark Molitor
Serial No. : 10/757,897
Page : 6

21. (currently amended) A vehicle suspension assembly, comprising:

a first control arm having a first end and a second end, wherein the first end of the first control arm is adapted to be pivotally coupled to a first frame member of a vehicle, and wherein the second end of the first control arm is adapted to be pivotally coupled to an axle of ~~the~~ a vehicle;

a second control arm having a first end and a second end, wherein the first end of the second control arm is adapted to be pivotally coupled to the first frame member of ~~the~~ a vehicle, and wherein the second end of the second control arm is adapted to be pivotally coupled to ~~the~~ an axle of ~~the~~ a vehicle;

a rigid first torsional member coupled to the first control arm along a length of the first control arm, and coupled to the second control arm along a length of the second control arm; and

a third control arm having a first end and a second end, wherein the first end of the third control arm is adapted to be pivotally coupled to a select one of the first frame member, a second frame member, and a third frame member of ~~the~~ a vehicle, and wherein the second end of the third control arm is adapted to be pivotally coupled to ~~the~~ an axle of ~~the~~ a vehicle.

22. (original) The vehicle suspension assembly of claim 21, wherein the third control arm is positioned between the first and second control arms, and wherein the third control arm is pivotally coupled with the first frame member.

23. (original) The vehicle suspension assembly of claim 21, wherein the torsional member is tube-shaped.

24. (currently amended) The vehicle suspension assembly of claim 21, wherein the first end of the first control arm is adapted to be pivotally coupled with a first linkage member that is fixedly attached to and extends upwardly from ~~the~~ an axle.

Applicant : Mark Molitor

Serial No. : 10/757,897

Page : 7

25. (currently amended) The vehicle suspension assembly of claim 24, wherein the first end of the second control arm is adapted to be pivotally coupled with a second linkage member that is fixedly attached to and extends upwardly from ~~the~~ an axle.

26. (original) The vehicle suspension assembly of claim 21, wherein the first and second end of the first control arm and the first and second end of the second control arm each include an elastically deformable bushing.

27. (original) The vehicle suspension assembly of claim 26, wherein the first and second end of the third control arm each include an elastically deformable bushing.

28. (currently amended) The vehicle suspension assembly of claim 21, wherein the first end of the third control arm is adapted to be pivotally coupled to the second frame member, and further including:

a fourth control arm having a first end and a second end, wherein the first end of the fourth control arm is adapted to be pivotally coupled to the third frame member of ~~the~~ a vehicle, and wherein the second end of the fourth control arm is adapted to be pivotally coupled to ~~the~~ an axle of ~~the~~ a vehicle.

29. (original) The vehicle suspension assembly of claim 21, wherein the torsional member is pivotally coupled to the first control arm, and wherein the first torsional member is pivotally coupled to the second control arm.

30. (original) The vehicle suspension assembly of claim 29, wherein the first torsional member is pivotable with respect to the first and second control arms in a substantially vertical direction.

Applicant : Mark Molitor
Serial No. : 10/757,897
Page : 8

31. (original) The vehicle suspension assembly of claim 30, wherein the first torsional member is pivotable with respect to the first and second control arms in a substantially horizontal direction.

32. (new) A vehicle suspension assembly, comprising:

a first control arm having a first end and a second end, wherein the first end of the first control arm includes a first bushing adapted to pivotally couple the first control arm to a first frame member of a vehicle, and wherein the second end of the first control arm is adapted to be pivotally coupled to an axle of a vehicle;

a second control arm having a first end and a second end, wherein the first end of the second control arm includes a second bushing adapted to pivotally couple the second control arm to a second frame member of a vehicle, and wherein the second end of the second control arm is adapted to be pivotally coupled to an axle of a vehicle; and

a rigid first torsional member coupled to the first control arm along a length of the first control arm rearward of the first bushing and forward of an axle, and coupled to the second control arm along a length of the second control arm rearward of the second bushing and forward of an axle.